

Products to go

... lead time 48 hours!

DL 185 – round modular recessed downlight



Description	
Lamp	TC-DEL
Socket	G24q
Ballast	high-frequency
Diameter	185 mm
Ceiling cut-out	172 mm +/- 2 mm
Recessed height	95 mm
Order quantity	max. 50 numbers

Version	Article Code
2 x 18 Watt	185.72.18.53

DL 185 – round modular recessed downlight



Description	
Lamp	TC-DEL
Socket	G24q
Ballast	high-frequency
Diameter	185 mm
Ceiling cut-out	172 mm +/- 2 mm
Recessed height	155 mm
Order quantity	max. 50 numbers

Version	Article Code
2 x 18 Watt	185.52.18.53

DL 220 – round modular recessed downlight



Description	
Lamp	TC-DEL
Socket	G24q
Ballast	high-frequency
Diameter	220 mm
Ceiling cut-out	206 mm +/- 2 mm
Recessed height	95 mm
Order quantity	max. 50 numbers

Version	Article Code
2 x 18 Watt	220.72.18.53

DL 220 – round modular recessed downlight



Description	
Lamp	TC-DEL
Socket	G24q
Ballast	high-frequency
Diameter	220 mm
Ceiling cut-out	206 mm +/- 2 mm
Recessed height	155 mm
Order quantity	max. 50 numbers

Version	Article Code
2 x 26 Watt	220.52.26.53

DL 255 – round modular recessed downlight



Description	
Lamp	TC-DEL
Socket	G24q
Ballast	high-frequency
Diameter	255 mm
Ceiling cut-out	238 mm +/- 2 mm
Recessed height	95 mm
Order quantity	max. 50 numbers

Version	Article Code
2 x 26 Watt	255.72.26.53

Suspended frosted glass (outer rim 10 mm clear)




for DL 185	185.903
for DL 220	220.903
for DL 255	255.903
Order quantity	max. 50 numbers

Frosted IP44 glass




for DL 185	185.900
for DL 220	220.900
for DL 255	255.900
Order quantity	max. 50 numbers

DM 225 – Square modular recessed downlight



Description	
Lamp	TC-DEL
Socket	G24q
Ballast	high-frequency
Diameter	226 mm
Ceiling cut-out	210 mm +/- 2 mm
Recessed height	155 mm
Order quantity	max. 50 numbers

Also in IP44 available!

Inlayed glass	
frosted	225.900
clear	225.901

Version	Article Code
2 x 26 Watt	225.52.26.53M

AS 13 – Track Light



Description	
Lamp	HIT-TC-CE
Socket	G8,5
Ballast	high-frequency
Colour	RAL 9016 structure
Dimensions (LxWxH)	165 x 100 x 190 mm
Order quantity	max. 20 numbers

Version	Spot - 2 x 6°	Medium - 2 x 12°	Flood - 2 x 24°
35 Watt	13.453.35.23-10	13.463.35.23-10	13.473.35.23-10
70 Watt	13.453.70.23-10	13.463.70.23-10	13.473.70.23-10

SL 624 – Free standing luminaire with micro prism diffuser



Description	
Lamp	TC-L
Socket	2G11
Ballast	high-frequency
Optic	micro prism diffuser
Colour	RAL 9006 structure
Order quantity	max. 20 numbers

Dimensions (LxWxH)	Version	Article Code
660 x 330 x 1900 mm	4 x 55 Watt	624.764.55.3-18

SL 730 – Free standing luminaire with micro prism diffuser



Description	
Lamp	TC-L
Socket	2G11
Ballast	high-frequency
Optic	micro prism diffuser
Colour	RAL 9006 structure
Order quantity	max. 20 numbers

Dimensions (LxWxH)	Version	Article Code
645 x 350 x 1900 mm	4 x 55 Watt	730.764.55.3-18

SL 740 – Pendant luminaire with micro prism diffuser



Description	
Lamp	T5
Socket	G5
Ballast	high-frequency
Optic	micro prism diffuser
Colour	RAL 9006 structure
Order quantity	max. 20 numbers

Dimensions (LxWxH)	Version	Article Code
54 W 1200x250x40 mm	2 x 54 Watt	740.462.54.3-18
80 W 1500x250x40 mm	2 x 80 Watt	740.462.80.3-18

SL 740 – Free standing luminaire with micro prism diffuser



Description	
Lamp	TC-L
Socket	2G11
Ballast	high-frequency
Optic	micro prism diffuser
Colour	RAL 9006 structure
Order quantity	max. 20 numbers

Dimensions (LxWxH)	Version	Article Code
645 x 312 x 1900 mm	4 x 55 Watt	740.764.55.3


SL 624 – Pendant luminaire with double parabolic louvre



Description	
Lamp	T5
Socket	G5
Ballast	high-frequency
Optic	double parabolic louvre
Colour	RAL 9006 structure
Order quantity	max. 20 numbers

Dimensions (LxWxH)	Version	Article Code
54 W 1238 x 90 x 38 mm	2 x 54 Watt	624.482.54.3-18
80 W 1538 x 90 x 38 mm	2 x 80 Watt	624.482.80.3-18

SL 624 – Pendant luminaire with double parabolic louvre



Description	
Lamp	T5
Socket	G5
Ballast	high-frequency
Optic	double parabolic louvre
Colour	RAL 9006 structure
Order quantity	max. 20 numbers

Dimensions (LxWxH)	Version	Article Code
54 W 1238 x 90 x 38 mm	3 x 54 Watt	624.483.54.3-18
80 W 1538 x 90 x 38 mm	3 x 80 Watt	624.483.80.3-18