


AB 310 – with frosted safety glass

Round surface mounted downlight for TC-DEL / TC-TEL lamps

Flat round surface mounted downlight for TC-DEL / TC-TEL lamps. Housing made of galvanised sheet steel, powder-coated in RAL 9016 with structure. Suspended frosted glass accessory with 10 mm clear outer rim. Max. weight: 2,2 kg




Version	High frequency ballast (HF)	Analogue dimmable HF ballast (1-10V)	Digital dimmable HF ballast (DALI)	Diameter	Height	Socket type
TC-DEL / TC-TEL 2 x 13 W	310.62.13.53	310.62.13.54	310.62.13.56	354 mm	75 mm	G24q
TC-DEL / TC-TEL 2 x 18 W	310.62.18.53	310.62.18.54	310.62.18.56	354 mm	75 mm	G24q
TC-DEL / TC-TEL 2 x 26 W	310.62.26.53	310.62.26.54	310.62.26.56	354 mm	75 mm	G24q




Attachments (Please order separately!)

Emergency light kit 3h*	310.0900
Emergency light kit 1h*	310.0901
Cover special colour	310.0090

* LED supplied loose and is only on request assembled to luminaire.



TC-DEL 2 x 18 W
Half-value angle 2 x 55°
Critical radiation angle/1000 cd/m² 90°
Light output ratio 47%



TC-DEL 2 x 26 W
Half-value angle 2 x 55°
Critical radiation angle/1000 cd/m² 90°
Light output ratio 47%