


AB 315

Round surface mounted downlight for TC-DEL / TC-TEL lamps

Round surface mounted downlight for TC-DEL / TC-TEL lamps. Housing made of galvanised sheet steel, powder-coated in RAL 9016 with structure. Reflector made of high-polished metalised pure aluminium. Glass accessory should be ordered with the luminaire. Aa retro fitting is not possible. Max. weight: 3,3 kg




Version	High frequency ballast (HF)	Analogue dimmable HF ballast (1-10V)	Digital dimmable HF ballast (DALI)	Diameter	Height	Socket type
TC-DEL / TC-TEL 2 x 18 W	315.62.18.53	315.62.18.54	315.62.18.56	354 mm	130 mm	G24q
TC-DEL / TC-TEL 2 x 26 W	315.62.26.53	315.62.26.54	315.62.26.56	354 mm	130 mm	G24q
TC-TEL 2 x 32 W	315.62.32.63	315.62.32.64	315.62.32.66	354 mm	130 mm	Gx24q




Attachments (Please order separately!)

Emergency light socket for two lamps	315.0562
Emergency light kit 3h*	315.0900
Emergency light kit 1h*	315.0901
Cover special colour	315.0090

* LED supplied loose and is only on request assembled to luminaire.



TC-DEL 2 x 18 W
 Half-value angle 2 x 45°
 Shielding angle 13°
 Critical radiation angle/1000 cd/m² 79°
 Light output ratio 72%



TC-DEL 2 x 26 W
 Half-value angle 2 x 44°
 Shielding angle 13°
 Critical radiation angle/1000 cd/m² 79°
 Light output ratio 77%

Decor attachment (You will find a detailed decor attachment description on page 393!)



315.603



315.604



315.640



315.680