



## AB 380 – with frosted safety glass


Round surface mounted downlight for TC-DEL / TC-TEL and T16-R lamps

Round surface mounted downlight with inlayed frosted glass pane for TC-DEL / TC-TEL and T16-R lamps. Housing made of galvanised steel sheet, powder-coated in RAL 9006 structure.

Max. weight: 2,5 kg




Version	High frequency ballast (HF)	Analogue dimmable HF ballast (1-10V)	Digital dimmable HF ballast (DALI)	Diameter	Height	Socket type
TC-DEL / TC-TEL 2 x 18 W	<b>381.602.18.53</b>	<b>381.602.18.54</b>	<b>381.602.18.56</b>	355 mm	100 mm	G24q
TC-DEL / TC-TEL 2 x 26 W	<b>381.602.26.53</b>	<b>381.602.26.54</b>	<b>381.602.26.56</b>	355 mm	100 mm	G24q
T16-R 40 W	<b>381.601.40.53</b>	<b>381.601.40.54</b>	<b>381.601.40.56</b>	355 mm	100 mm	2GX13
T16-R 55 W	<b>381.601.55.53</b>	<b>381.601.55.54</b>	<b>381.601.55.56</b>	355 mm	100 mm	2GX13
T16-R 22+40 W	<b>381.602.62.53</b>			355 mm	100 mm	2GX13



### Attachments (Please order separately!)

Emergency light socket for one lamp	<b>381.0561</b>
Emergency light socket for two lamps	<b>381.0562</b>
Cover special colour	<b>381.0090</b>




#### TC-DEL 2 x 18 W

Half-value angle 2 x 50°

Critical radiation angle/1000 cd/m<sup>2</sup> 90°

Light output ratio 43%




#### T16-R 55 W

Half-value angle 2 x 50°

Critical radiation angle/1000 cd/m<sup>2</sup> 90°

Light output ratio 35%




# AB 380 – with frosted safety glass

Round surface mounted downlight for TC-DEL / TC-TEL and T16-R lamps

Round surface mounted downlight with inlayed, curved frosted glass pane for TC-DEL / TC-TEL and T16-R lamps. Housing made of galvanised steel sheet, powder-coated in RAL 9006 structure. Max. weight: 2,9 kg




Version	High frequency ballast (HF)	Analogue dimmable HF ballast (1-10V)	Digital dimmable HF ballast (DALI)	Diameter	Height	Socket type
TC-DEL / TC-TEL 2 x 18 W	<b>381.612.18.53</b>	<b>381.612.18.54</b>	<b>381.612.18.56</b>	355 mm	80 mm	G24q
TC-DEL / TC-TEL 2 x 26 W	<b>381.612.26.53</b>	<b>381.612.26.54</b>	<b>381.612.26.56</b>	355 mm	80 mm	G24q
T16-R 40 W	<b>381.611.40.53</b>	<b>381.611.40.54</b>	<b>381.611.40.56</b>	355 mm	80 mm	2GX13
T16-R 55 W	<b>381.611.55.53</b>	<b>381.611.55.54</b>	<b>381.611.55.56</b>	355 mm	80 mm	2GX13




### Attachments (Please order separately!)

Emergency light socket for one lamp	<b>381.0561</b>
Emergency light socket for two lamps	<b>381.0562</b>
Cover special colour	<b>381.0090</b>



**TC-DEL 2 x 18 W**  
 Half-value angle 2 x 55°  
 Critical radiation angle/1000 cd/m² 90°  
 Light output ratio 43%



**T16-R 55 W**  
 Half-value angle 2 x 50°  
 Critical radiation angle/1000 cd/m² 50°  
 Light output ratio 31%

Round surface mounted downlights