



## Super flat round recessed downlight

- Recessed height: 50 mm
- Metalised, high-quality reflectors made of pure aluminium (Al 99,98)
- The troubleshooter for low ceiling heights
- Ceiling plate thickness from 1-10 mm





# DL 255 XF – Recessed height 50 mm

## Super flat recessed downlight for TC-DEL / TC-TEL lamps


Super flat recessed downlight for TC-DEL / TC-TEL lamps. The ceiling trim is made of white powder-coated steel sheet. Luminaire with tool-less exchangeable remote gear box. Housing manufactured from galvanised sheet steel. Reflector made of high-polished metalised pure aluminium. Decor glasses should be ordered with the luminaire as retro fitting is not possible. Max. weight: 1,8 kg



Version	High frequency ballast (HF)	Analogue dimmable HF ballast (1-10V)	Digital dimmable HF ballast (DALI)	Diameter	Ceiling cut-out	Recessed height	Socket type
TC-DEL / TC-TEL 2 x 13 W	<b>255.72.13.53XF</b>			255 mm	238 mm	50 mm	G24q
TC-DEL / TC-TEL 2 x 18 W	<b>255.72.18.53XF</b>	<b>255.72.18.54XF</b>	<b>255.72.18.56XF</b>	255 mm	238 mm	50 mm	G24q
TC-DEL / TC-TEL 2 x 26 W	<b>255.72.26.53XF</b>	<b>255.72.26.54XF</b>	<b>255.72.26.56XF</b>	255 mm	238 mm	50 mm	G24q



**TC-DEL 2 x 18 W**  
 Half-value angle 2 x 55°  
 Shielding angle 8°  
 Critical radiation angle/1000 cd/m² 90°  
 Light output ratio 71%



**TC-DEL 2 x 26 W**  
 Half-value angle 2 x 55°  
 Shielding angle 8°  
 Critical radiation angle/1000 cd/m² 90°  
 Light output ratio 74%

### Decor attachment



255.903D

Round recessed downlights