

EM 28


LED rescue sign luminaire for recessed mounting



LED rescue sign luminaire (1,1 W) with transformer for recessed mounting. Housing made of galvanised sheet steel, powder-coated. Twofold acrylic pane with white symbol on green ground, one-sided or two-sided inscribed. Suitable for facilities according to EN 50172. Identification distance 29 m. Max. weight: 2,0 kg

Version	with single battery	for central battery	Length x width x height	Ceiling cut-out	Recessed height
LED 1,1 W	28.111.02.E-18	28.111.02.Z-18	365 x 100 x 190 mm	355 x 90 mm	30 mm

If you require the luminaire in white (RAL 9016 structure) please use „-10“ instead of „-18“.



Attachments (Please order separately!)

LED and switch-key for single battery	39.0932
Selftest for single battery with LED	39.041
Concrete casting drum	28.2035

Pictograph (Please note article code on your order!)



E11-1 one-sided
E11-2 two-sided



E12-1 one-sided
E12-2 two-sided



E13-1 one-sided
E13-2 two-sided

EM 28


LED rescue sign luminaire for surface mounting



LED rescue sign luminaire (1,1 W) with transformer for surface mounting. Housing made of galvanised sheet steel, powder-coated. Twofold acrylic pane with white symbol on green ground, one-sided or two-sided inscribed. Suitable for facilities according to EN 50172. Identification distance 29 m. Max. weight: 2,0 kg

Version	with single battery	for central battery	Length x width x height
LED 1,1 W	28.131.02.E-18	28.131.02.Z-18	360 x 80 x 190 mm

If you require the luminaire in white (RAL 9016 structure) please use „-10“ instead of „-18“.



Attachments (Please order separately!)

LED and switch-key for single battery	39.0932
Selftest for single battery with LED	39.041

Pictograph (Please note article code on your order!)



E11-1 one-sided
E11-2 two-sided



E12-1 one-sided
E12-2 two-sided



E13-1 one-sided
E13-2 two-sided