




## SL 740

Wall luminaire

- Housing made of extruded aluminium profile, end caps made of die-cast aluminium, powder-coated in RAL 9006 with structure.
- Micro prism or frosted acrylic diffuser
- Available with dimmable HF ballast or emergency kits on request
- Compatible pendant, free standing and surface mounted luminaire

## SL 740

Wall luminaire with micro prism diffuser



Wall luminaire with micro prism diffuser for indirect and diffuse-direct lighting for TC-L lamps. Housing made of extruded aluminium profile, end caps made of die-cast aluminium, powder-coated in RAL 9006 with structure. Max. weight: 4,5 kg

Version	RAL 9006 structure	Length x width x height	Socket type
TC-L 2 x 55 W c/w HF ballast	<b>740.362.55.3</b>	605 x 183 x 40 mm	2G11

### Attachments (Please order separately!)

Special colour	<b>740.0090</b>
----------------	-----------------

## SL 740

Wall luminaire with frosted acrylic diffuser



Wall luminaire with frosted acrylic diffuser for indirect and diffuse-direct lighting for TC-L lamps. Housing made of extruded aluminium profile, end caps made of die-cast aluminium, powder-coated in RAL 9006 with structure. Max. weight: 4,5 kg

Version	RAL 9006 structure	Length x width x height	Socket type
TC-L 2 x 55 W c/w HF ballast	<b>740.392.55.3</b>	605 x 183 x 40 mm	2G11

### Attachments (Please order separately!)

Special colour	<b>740.0090</b>
----------------	-----------------