

## SL 740

Surface mounted luminaire for T5 lamps

- Housing made of extruded aluminium profile, end caps made of die-cast aluminium, powder-coated in RAL 9006 with structure
- Surface mounted frame made of sheet steel, powder coated in RAL 9016 structure
- Micro prism or frosted acrylic diffuser
- Unobtrusive ceiling lucency by indirect light portion
- Easy maintenance by flap mechanism
- Compatible pendant, free-standing and wall luminaire



## SL 740

### Surface mounted luminaire with micro prism diffuser


Surface mounted luminaire with micro prism diffuser for diffuse-direct lighting for T5 lamps. Housing made of extruded aluminium profile, end caps made of die-cast aluminium, powder-coated in RAL 9006 with structure. Surface mounted frame made of sheet steel with flap mechanism, powder-coated in RAL 9016 with structure.

Max. weight: 5,0 kg



#### Surface: RAL 9006 structure

Version	High frequency ballast (HF)	Digital dimmable HF ballast (DALI)	Length x width x height	Socket type
T5 2 x 28 / 54 W	<b>740.662.54.3</b>	<b>740.662.54.6</b>	1200 x 250 x 70 mm	G5
T5 2 x 35 / 49 / 80 W	<b>740.662.80.3</b>	<b>740.662.80.6</b>	1500 x 250 x 70 mm	G5



T5 2 x 54 W  
indirect / direct 15 / 85%  
UGR 14,0 / 17,5  
Critical radiation angle/1000 cd/m<sup>2</sup> 90°  
Light output ratio 50%

#### Attachments (Please order separately!)

Emergency light kit 1h	<b>740.0901</b>
Emergency light kit 3h	<b>740.0900</b>
Special colour	<b>740.0090</b>

## SL 740

### Surface mounted luminaire with frosted acrylic diffuser


Surface mounted luminaire with frosted acrylic diffuser for diffuse-direct lighting for T5 lamps. Housing made of extruded aluminium profile, end caps made of die-cast aluminium, powder-coated in RAL 9006 with structure. Surface mounted frame made of sheet steel with flap mechanism, powder-coated in RAL 9016 with structure.

Max. weight: 5,0 kg



#### Surface: RAL 9006 structure

Version	High frequency ballast (HF)	Digital dimmable HF ballast (DALI)	Length x width x height	Socket type
T5 2 x 28 / 54 W	<b>740.692.54.3</b>	<b>740.692.54.6</b>	1200 x 250 x 70 mm	G5
T5 2 x 35 / 49 / 80 W	<b>740.692.80.3</b>	<b>740.692.80.6</b>	1500 x 250 x 70 mm	G5



T5 2 x 54 W  
indirect / direct 10 / 90%  
UGR 17,2 / 17,2  
Critical radiation angle/1000 cd/m<sup>2</sup> 90°  
Light output ratio 44%

#### Attachments (Please order separately!)

Emergency light kit 1h	<b>740.0901</b>
Emergency light kit 3h	<b>740.0900</b>
Special colour	<b>740.0090</b>