



## SL 640

Recessed luminaire for T5 lamps

- For metal and fireproof ceilings
- Housing made of sheet steel powder-coated in RAL 9010
- Double parabolic louvre, frosted acrylic diffuser
- Double parabolic louvre made of pure aluminium (Al 99.98), matt-anodised

## SL 640


### Recessed luminaire with double parabolic louvre

Recessed luminaire for metal and fireproof ceilings with double parabolic louvre for T5 lamps. Housing made of sheet steel powder-coated in RAL 9010. Double parabolic louvre made of pure aluminium (Al 99.98), matt-optic. Max. weight: 3,9 kg



#### Surface: RAL 9016 structure

Version	High frequency ballast (HF)	Digital dimmable HF ballast (DALI)	Length x width x height	Ceiling cut-out	Recessed height	Socket type
T5 2 x 21 / 39 W	<b>640.82.21.3</b>	<b>640.82.21.6</b>	915 x 172 x 50 mm	903 x 164 mm	50 mm	G5
T5 2 x 28 / 54 W	<b>640.82.28.3</b>	<b>640.82.28.6</b>	1215 x 172 x 50 mm	1203 x 164 mm	50 mm	G5
T5 2 x 35 / 49 W	<b>640.82.35.3</b>	<b>640.82.35.6</b>	1515 x 172 x 50 mm	1503 x 164 mm	50 mm	G5



## SL 640

### Recessed luminaire with frosted acrylic diffuser

Recessed luminaire for metal and fireproof ceilings with frosted acrylic diffuser for T5 lamps. Housing made of sheet steel powder-coated in RAL 9010. Max. weight: 3,9 kg



#### Surface: RAL 9016 structure

Version	High frequency ballast (HF)	Digital dimmable HF ballast (DALI)	Length x width x height	Ceiling cut-out	Recessed height	Socket type
T5 1 x 21 / 39 W	<b>640.91.21.6</b>	<b>640.91.21.3</b>	915 x 172 x 50 mm	903 x 164 mm	50 mm	G5
T5 1 x 28 / 54 W	<b>640.91.28.6</b>	<b>640.91.28.3</b>	1215 x 172 x 50 mm	1203 x 164 mm	50 mm	G5
T5 1 x 35 / 49 W	<b>640.91.35.6</b>	<b>640.91.35.3</b>	1515 x 172 x 50 mm	1503 x 164 mm	50 mm	G5
T5 2 x 21 / 39 W	<b>640.92.21.6</b>	<b>640.92.21.3</b>	915 x 172 x 50 mm	903 x 164 mm	50 mm	G5
T5 2 x 28 / 54 W	<b>640.92.28.3</b>	<b>640.92.28.6</b>	1215 x 172 x 50 mm	1203 x 164 mm	50 mm	G5
T5 2 x 35 / 49 W	<b>640.92.35.3</b>	<b>640.92.35.6</b>	1515 x 172 x 50 mm	1503 x 164 mm	50 mm	G5

