

SL 790

Recessed luminaire for T5 lamps

- Housing made of extruded aluminium profile, end caps made of aluminium, powder-coated in RAL 9016 with structure
- Opal-white PMMA diffuser
- Polycarbonate diffuser as option available
- Emergency version
- Wall and ceiling installation
- Also in continuous mounted version available

SL 790



Recessed luminaire with opal-white PMMA diffuser

Recessed luminaire with opal-white PMMA diffuser for T5 lamps. Housing made of extruded aluminium profile, end caps made of aluminium, powder-coated in RAL 9016 with structure. Max. weight: 7 kg



Surface: RAL 9016 structure

Version	High frequency ballast (HF)	Digital dimmable HF ballast (DALI)	Length x width x height	Ceiling cut-out	Recessed height	Socket type
T5 1 x 14 / 24 W	790.591.24.3-10	790.591.24.6-10	620 x 117 x 90 mm	607 x 106 mm	115 mm	G5
T5 1 x 21 / 39 W	790.591.39.3-10	790.591.39.6-10	920 x 117 x 90 mm	907 x 106 mm	115 mm	G5
T5 1 x 28 / 54 W	790.591.54.3-10	790.591.54.6-10	1220 x 117 x 90 mm	1207 x 106 mm	115 mm	G5
T5 1 x 35 / 49 / 80 W	790.591.80.3-10	790.591.80.6-10	1520 x 117 x 90 mm	1507 x 106 mm	115 mm	G5
T5 2 x 28 W	790.592.28.3-10	790.592.28.6-10	1220 x 117 x 90 mm	1207 x 106 mm	115 mm	G5
T5 2 x 35 W	790.592.35.3-10	790.592.35.6-10	1520 x 117 x 90 mm	1507 x 106 mm	115 mm	G5



T5 1 x 54 W
UGR 19,1 / 19,6
Critical radiation angle/1000 cd/m² 90°
Light output ratio 57%

Attachments (Please order separately!)

Emergency light kit 1h	790.0901
Emergency light kit 3h	790.0900