




AS 23 LED

Track light

- Luminaire made of aluminium die-cast, powder-coated in RAL 9006 with structure, RAL 9016 with structure or RAL 9005 with structure
- Rotatable and adjustable
- Spherical facets reflector made of high-polished metalised pure aluminium (Al 99.98) with 4 different beam angles
- Track light could be operated in different wattages from 33 up 50 Watt (factory setting 33, 42, 50 W).
- Deliverable in light colour 2.700 K, 3.000 K, 4.000 K and 6.000 K
- Incl. universal adapter for 3-phases track

AS 23 LED

Track light with LED technology



Track light with high-power LED 50 W. Rotatable up to 360° and adjustable up to 90°. Track light made of die-cast aluminium, powder-coated. Adapter integrated in gear box with additional track interlock. Bezel with bayonet lock to allow an easy reflector and filter exchange. High brilliant spherical facets reflector made of pure aluminium for maximum LOR and neutral colour rendering in 4 different beam angles (spot, medium, flood and wideflood). Track light could be operated in different wattages from 33 up 50 Watt (factory setting 33, 42, 50 W). Electronically regulated cooling with high-power „whispering“ fan. Deliverable in light colour 2.700 K, 3.000 K, 4.000 K and 6.000 K. Colour rendering index Ra > 82. Max. weight: 2.0 kg

Reflector: spot - 2 x 8°

Version	RAL 9006 structure	Length x width x height
LED 50 W, 2700 K	23.453.502-18	256 x 126 x 235 mm
LED 50 W, 3000 K	23.453.503-18	256 x 126 x 235 mm
LED 50 W, 4000 K	23.453.504-18	256 x 126 x 235 mm
LED 50 W, 6000 K	23.453.506-18	256 x 126 x 235 mm

Reflector: medium - 2 x 12°

Version	RAL 9006 structure	Length x width x height
LED 50 W, 2700 K	23.463.502-18	256 x 126 x 235 mm
LED 50 W, 3000 K	23.463.503-18	256 x 126 x 235 mm
LED 50 W, 4000 K	23.463.504-18	256 x 126 x 235 mm
LED 50 W, 6000 K	23.463.506-18	256 x 126 x 235 mm

Reflector: flood - 2 x 16°

Version	RAL 9006 structure	Length x width x height
LED 50 W, 2700 K	23.473.502-18	256 x 126 x 235 mm
LED 50 W, 3000 K	23.473.503-18	256 x 126 x 235 mm
LED 50 W, 4000 K	23.473.504-18	256 x 126 x 235 mm
LED 50 W, 6000 K	23.473.506-18	256 x 126 x 235 mm

Reflector: wideflood - 2 x 27°

Version	RAL 9006 structure	Length x width x height
LED 50 W, 2700 K	23.483.502-18	256 x 126 x 235 mm
LED 50 W, 3000 K	23.483.503-18	256 x 126 x 235 mm
LED 50 W, 4000 K	23.483.504-18	256 x 126 x 235 mm
LED 50 W, 6000 K	23.483.506-18	256 x 126 x 235 mm

If you require the luminaire in white (RAL 9016 structure) please use „-10“ instead of „-18“, if you require the luminaire in black (RAL 9005 structure) please use „-11“ instead of „-18“. For any other RAL colour use „-9“.

Spot - LED 50 W, 4.000 K

h [m]	E(m) [lx]	Ø [m]
1,0	14879	0,29
2,0	3745	0,58
3,0	1684	0,86
4,0	936	1,15
5,0	599	1,44

∠α 2 x 8°

Medium - LED 50 W, 4.000 K

h [m]	E(m) [lx]	Ø [m]
1,0	7958	0,44
2,0	1990	0,87
3,0	884	1,31
4,0	497	1,74
5,0	318	2,18

∠α 2 x 12°

Flood - LED 50 W, 4.000 K

h [m]	E(m) [lx]	Ø [m]
1,0	5671	0,57
2,0	1418	1,13
3,0	630	1,70
4,0	354	2,26
5,0	227	2,83

∠α 2 x 16°

Wideflood - LED 50 W, 4.000 K

h [m]	E(m) [lx]	Ø [m]
1,0	2925	1,00
2,0	581	1,99
3,0	258	2,99
4,0	145	3,99
5,0	93	4,99

∠α 2 x 27°