

Optics

for high-bay luminaires



Conical lens

- Spreads the direct light portion to achieve a homogenous illumination
- With clamp for tool-less mounting

Version	Art.-No.	Dimensions (DxT)	Weight
PL 912	912.9000	316 x 3 mm	0.30 kg
PL 916	916.9000	416 x 3 mm	0.50 kg
PL 922	922.9000	516 x 3 mm	0.90 kg



1 decorative metal ring

- Metal ring, powder-coated in RAL 9006 structure
- Fixed with 3 brackets at the housing

Version	Art.-No.	Dimensions (DxH)	Weight
PL 912	912.9010	420 x 15 mm	0.65 kg



3 decorative metal rings

- 3 metal rings, powder-coated in RAL 9006 structure
- Fixed with 3 brackets at the housing

Version	Art.-No.	Dimensions (DxH)	Weight
PL 912	912.9030	420 x 15 mm	1.50 kg



1 decorative metal ring with frosted safety glass pane

- Diffuse light portion to achieve a homogenous illumination
- Metal ring, powder-coated in RAL 9006 structure
- Safety glass pane inlayed into metal ring
- Fixed with 3 brackets at the housing

Version	Art.-No.	Dimensions (DxH)	Weight
PL 912	912.9011	420 x 15 mm	1.30 kg