


# PL 910

## Pendant luminaire with aluminium reflector



Pendant luminaire with aluminium reflector. Housing made of galvanised sheet steel, powder-coated in RAL 9006 with structure. Faceted aluminium reflector made of high-polished pure aluminium (outside matt anodised). C/w steel wire suspension (20 m) and transparent mains supply. Max. weight: 3.3 kg



### 1 lamp

Version	RAL 9006 struktur	$\sphericalangle_{\alpha}$	Diameter	Height	Socket type
TC-TEL 26 W c/w HF ballast	<b>910.01.26.63</b>	13°	330 mm	450 mm	GX24q
TC-TEL 32 W c/w HF ballast	<b>910.01.32.63</b>	14°	330 mm	450 mm	GX24q
TC-TEL 42 W c/w HF ballast	<b>910.01.42.63</b>	14°	330 mm	450 mm	GX24q
TC-TEL 57 W c/w HF ballast	<b>910.01.57.63</b>	14°	330 mm	450 mm	GX24q
TC-TELI 60 W c/w HF ballast	<b>910.01.60.63</b>	21°	330 mm	450 mm	2G8
TC-TELI 85 W c/w HF ballast	<b>910.01.85.63</b>	22°	330 mm	450 mm	2G8
HIE 70 W c/w HF ballast	<b>910.01.70.223</b>	13°	330 mm	450 mm	E27
HIE 100 W c/w HF ballast	<b>910.01.10.223</b>	12°	330 mm	450 mm	E27

### Attachments (Please order separately!)

Wire suspension, 3 m with loop	<b>72430.3000</b>
Wire suspension, 5 m with loop	<b>72430.5000</b>
Ceiling rose, round, RAL 9006 structure	<b>900.001-18</b>