


PL 912

Pendant luminaire with prismatic reflector



Pendant luminaire with prismatic acrylic reflector. Housing made of galvanised sheet steel, powder-coated in RAL 9006 with structure. C/w steel wire suspension (2 m) and transparent mains supply. Max. weight: 3.5 kg



1 lamp

Version	RAL 9006 struktur	\sphericalangle_{α}	Diameter	Height	Socket type
TC-TEL 26 W c/w HF ballast	912.01.26.63	45°	316 mm	450 mm	GX24q
TC-TEL 32 W c/w HF ballast	912.01.32.63	50°	316 mm	450 mm	GX24q
TC-TEL 42 W c/w HF ballast	912.01.42.63	55°	316 mm	450 mm	GX24q
TC-TEL 57 W c/w HF ballast	912.01.57.63	65°	316 mm	450 mm	GX24q
TC-TELI 60 W c/w HF ballast	912.01.60.63	41°	316 mm	450 mm	2G8
TC-TELI 85 W c/w HF ballast	912.01.85.63	48°	316 mm	450 mm	2G8
HIE 70 W c/w HF ballast	912.01.70.223	42°	316 mm	450 mm	E27
HIE 100 W c/w HF ballast	912.01.10.223	40°	316 mm	450 mm	E27

2 lamps

Version	RAL 9006 struktur	\sphericalangle_{α}	Diameter	Height	Socket type
2 x TC-TEL 26 W c/w HF ballast	912.02.26.63	49°	316 mm	450 mm	GX24q
2 x TC-TEL 32 W c/w HF ballast	912.02.32.63	52°	316 mm	450 mm	GX24q
2 x TC-TEL 42 W c/w HF ballast	912.02.42.63	60°	316 mm	450 mm	GX24q
2 x TC-TEL 57 W c/w HF ballast	912.02.57.63	75°	316 mm	450 mm	GX24q


Attachments (Please order separately!)

Wire suspension, 3 m with loop	72430.3000
Wire suspension, 5 m with loop	72430.5000
Ceiling rose, round, RAL 9006 structure	900.001-18


Optics (You will find a detailed description on page 239!)



912.9000



912.9010



912.9011



912.9030