


PL 916

Pendant luminaire with prismatic reflector



Pendant luminaire with prismatic acrylic reflector. Housing made of galvanised sheet steel, powder-coated in RAL 9006 with structure. C/w steel wire suspension (2 m) and transparent mains supply. Max. weight: 6.9 kg



1 lamp

| Version | RAL 9006 struktur | \sphericalangle_{α} | Diameter | Height | Socket type |
|------------------------------|----------------------|----------------------------|----------|--------|-------------|
| TC-TEL 32 W c/w HF ballast | 916.01.32.63 | 46° | 416 mm | 535 mm | GX24q |
| TC-TEL 42 W c/w HF ballast | 916.01.42.63 | 51° | 416 mm | 535 mm | GX24q |
| TC-TEL 57 W c/w HF ballast | 916.01.57.63 | 59° | 416 mm | 535 mm | GX24q |
| TC-TELI 60 W c/w HF ballast | 916.01.60.63 | 42° | 416 mm | 535 mm | 2G8 |
| TC-TELI 85 W c/w HF ballast | 916.01.85.63 | 50° | 416 mm | 535 mm | 2G8 |
| TC-TELI 120 W c/w HF ballast | 916.01.12.63 | 62° | 416 mm | 535 mm | 2G8 |
| HIE 150 W c/w HF ballast | 916.01.15.223 | 40° | 416 mm | 535 mm | E27 |

2 lamps

| Version | RAL 9006 struktur | \sphericalangle_{α} | Diameter | Height | Socket type |
|--------------------------------|---------------------|----------------------------|----------|--------|-------------|
| 2 x TC-TEL 26 W c/w HF ballast | 916.02.26.63 | 45° | 416 mm | 535 mm | GX24q |
| 2 x TC-TEL 32 W c/w HF ballast | 916.02.32.63 | 48° | 416 mm | 535 mm | GX24q |
| 2 x TC-TEL 42 W c/w HF ballast | 916.02.42.63 | 52° | 416 mm | 535 mm | GX24q |
| 2 x TC-TEL 57 W c/w HF ballast | 916.02.57.63 | 60° | 416 mm | 535 mm | GX24q |

Attachments (Please order separately!)

| | |
|---|-------------------|
| Wire suspension, 3 m with loop | 72430.3000 |
| Wire suspension, 5 m with loop | 72430.5000 |
| Ceiling rose, round, RAL 9006 structure | 900.001-18 |

Optics (You will find a detailed description on page 239!)



916.9000